



VHF RADIOTELEPHONE

JHS-770S/780D



— a first class VHF with an advanced modular design that allows for maximum installation flexibility

- Direct call by AIS™**
- Easy operation with JOG dial**
- Intercom & loudhailer function**
- 3.8" high brightness LCD screen**
- 120 seconds recording**

VHF series

– performance features

Unique features

- Available as semi-duplex or full-duplex, this class A VHF radiotelephone incorporates advanced modular design that allows for maximum installation flexibility.



Direct call by AIS™

When connecting your AIS to the new VHF, new possibilities become available. This innovative feature, unique to JRC, allows you with one push of the button, to quickly navigate through a list of targets in your surrounding area. Bearing, range and MMSI information of target vessels are sorted from the shortest range upwards. You can now easily select the vessel you wish to get in contact with, and send a DSC message immediately.

Intercom and loudhailer

The VHF radiotelephone has an intercom functionality for easy communication with multiple other VHF controllers onboard! Additionally, to always be in full control and on top of communication with deck or dock hands, a loudhailer function is built in. An optional external speaker with amplifier increases talk power, making your messaging loud and clear, thereby adding to the safety of the vessel.

Clear display

Improved visibility is realised by the integrated 3.8" high brightness silver LCD screen with excellent sunlight viewability. The main data is displayed in large characters for easy reading.

Extendable up to 5 controllers

The VHF series configuration allows having up to 5 controllers covering various important sections onboard. Additionally, there is a range of possibilities for connecting extra handsets and printers.

120 seconds digital recording

JRC has included a recording function for the last 120 seconds of open squelch (voice).

In situations where loud engines or other background noises disrupt your reception, this characteristic feature enables you to immediately repeat any unclear messages.



VHF series – developed for maximum ease of use

Wing controller

For wing and/or outside applications, JRC has developed an optional, simplified channel selector. This compact weatherproof unit allows basic operation, such as channel and power selection, and has a channel 16 preset.



Easy configuration

The JHS-770S/780D is developed upon maximum flexibility, having a separate transceiver and controller allowing flexible installation in confined spaces. Either panel, desktop or overhead mounting is possible with this size reduced VHF radiotelephone.

Easy operation

The combination of push buttons and JOG dial operation, together with JRC's innovative software including easy menu structures ensures logical, accurate and convenient operation.



Simplified squelch and volume operation

Direct call by AIS™


Easy JOG dial operation

StarNetwork™

JRC has been providing sales and support of products since 1915! Today, JRC offers comprehensive support through its organisation, in partnership with a world-wide StarNetwork™ of over 270 fully qualified agents, giving support 24 hours a day, 7 days a week, and 365 days a year!




VHF series - system flexibility




¹optional products

Dimension drawings¹ - Power supply, Channel selector, Connection box


NBD-865
MASS 6.1kg



NCM-2000
MASS 0.6kg




NQD-2770
MASS 1.3kg




Dimension drawings² - Handset connection box, Speaker

NQE-1846
MASS 1.1kg
WATERPROOF
WALL MOUNT


*Flush mount type
(NQE-1845)
available



NQE-1847
MASS 0.3kg
FLUSH MOUNT




NVS-423
MASS 1.1kg
WALL MOUNT




Dimension drawings³ - Printer

NKG-91
MASS 0.75kg
WALL MOUNT



DPU-414
MASS 0.6kg
TABLE MOUNT





^{1,2,3}optional products

VHF series – dimensions and weights



Dimension drawings - Controller

NCM-1770 MASS 1.3kg





Dimension drawings - Transceiver, Antenna



NTE-770S MASS 6.3kg
NTE-780D MASS 6.9kg



7ABJD0004
MASS 0.3kg



Dimension drawings - Handset



VHF series

– specifications

Model	JHS-770S	JHS-780D
GMDSS compliance		✓
General		
Communication mode	simplex/semi-duplex	simplex/duplex
Frequency range	155.00 - 163.50MHz	
TX	155.00 - 163.50MHz (simplex/semi-duplex), 156.00 - 157.45MHz (duplex)	
RX	155.00 - 163.50MHz (simplex/semi-duplex), 160.60 - 162.05MHz (duplex)	
Output power	25W/1W	
Modulation type	radiotelephone G3E/F3E, DSC/ATIS G2B/F2B	
Channel spacing	25kHz	
Frequency accuracy	within $\pm 10 \times 10^{-6}$	
Antenna impedance	50Ω unbalanced	
DSC CH70 receiver	built in	
DSC CH70 frequency	156.525MHz	
DSC received message LOG	20 distress messages 20(TX)+20(RX) non-distress messages	
Channel capacity		
ITU/USA/Canada	57 channels max	
Inland Waterway	57 channels max	
Private	200 channels max (channel steps: 25kHz, 12.5kHz, 10kHz)	
Weather	10 channels max	
Memory	10 channels max	
Inputs		
IEC-61162-1	GPS	
IEC-61162-2	AIS	
Outputs		
IEC-61162-1	VDR/S-VDR	
Audio	600Ω 0dBm balanced (to VDR/S-VDR), unbalanced (to ext. loudspeaker)	
RS232C	for external printer NKG-91 and DPU-414	
Environmental conditions		
Power voltage	DC 24V +30% -10%	
Current consumption	DC 24V input, 8.3A max	
Ambient condition	temperature: -15°C +55°C (range for full performance 0°C +40°C)	
Optional items		
Power supply unit	NBD-865 (for AC operation)	
Remote VHF controller	NCM-1770(with handset, cradle and cable)	
VHF channel selector	NCM-2000	
Controller connection box	NQD-2770	
Flush mounting kit	MPBC42957(for NCM-1770)	
Controller bracket	MPBX44354	
Handset	NQW-261 (with cradle)	
Handset connection box	NQE-1847	
Handset connection box (waterproof)	NQE-1845(flush mount) / NQE-1846(wall mount)	
Printer (table mount)	DPU-414	
Printer (flush mount)	NKG-91	
External speaker (wall mount)	NVS-423	
External speaker (flush mount)	NVS-423A	
Extension board	CQD-7701 (required for multiple controllers)	

• Specifications may be subject to change without notice.

For further information, contact:



Since 1915

Japan Radio Co., Ltd.

URL <http://www.jrc.co.jp/eng/>

Main Office: NAKANO CENTRAL PARK EAST
10-1, Nakano 4-chome, Nakano-ku, Tokyo
164-8570, Japan
Telephone: +81-3-6832-1816
Facsimile: +81-3-6832-1845

Overseas Branches : Seattle, Amsterdam, Athens, Manila
Liaison Offices : Taipei, Jakarta, Singapore, Hanoi,
New York

Overseas Subsidiaries : Shanghai, Rio de Janeiro

31EM

ISO9001, ISO14001 Certified